

Page 1/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

	ardous chemical and of the supplier
Product identifier	
Trade name Recommended use of the chemical and restrictions on	Konudur 250 OM-PL Sommerharz - Komponente A No further relevant information available.
use Application of the substance / the mixture	
	•
Details of the supplier of the s Manufacturer/Supplier:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de
	MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
Informing department:	msds@mc-bauchemie.de
	ce or mixture
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin	irritation.
<i>Classification of the substand</i> Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serio	irritation.
<i>Classification of the substand</i> Skin Irrit. 2 H315 Causes skin	irritation.
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serio Label elements GHS label elements	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS).
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serio Label elements GHS label elements Hazard pictograms	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serid Label elements GHS label elements Hazard pictograms Signal word	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS).
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serio Label elements GHS label elements Hazard pictograms	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 Danger Silicic acid, sodium salt H315 Causes skin irritation.
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serid Label elements GHS label elements Hazard pictograms Signal word Hazard-determining components of labelling:	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 Danger Silicic acid, sodium salt
Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serie Label elements GHS label elements Hazard pictograms Signal word Hazard-determining components of labelling: Hazard statements	n irritation. ous eye damage. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 Danger Silicic acid, sodium salt H315 Causes skin irritation. H318 Causes serious eye damage. P280 Wear protective gloves / eye protection / fa



Page 2/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

	P321 P332+P313	(Contd. of page 1) Specific treatment (see on this label). If skin irritation occurs: Get medical advice/ attention.
	P362	Take off contaminated clothing and wash before reuse.
 Other hazards Results of PBT and vF 	PvB assessment	
· PBT: · vPvB:	Not applicable. Not applicable.	

3 Composition and information of the ingredients of the hazardous chemical

- · Chemical characterisation: Mixtures
- **Description:** Mixture consisting of the following components.

· Dangerous components:				
CAS: 1344-09-8	Silicic acid, sodium salt	Eye Dam. 1, H318; Skin Irrit. 2, H315	30-60%	
CAS: 107-21-1	Ethanediol	Acute Tox. 4, H302	<10%	
· Additional infor	mation For the wordin	g of the listed hazard phrases refer to sect	ion 16.	

4 First-aid measures

Description of first aid measu General information	Remove, decontaminate and dispose of soiled, soaked clothing
	and shoes immediately.
After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
After skin contact	In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.
After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
After swallowing	Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
Information for doctor Most important symptoms and effects, both acute and	
delayed	Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary. (Contd. on page 3)



Page 3/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

(Contd. of page 2)

MY

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

 Indication of any immediate medical attention and special treatment needed No infor

No information available.

5 Fire-fighting measures

• Extinguishing media

• Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- Special hazards arising from the substance or mixture
 Advice for firefighters
- · Protective equipment:
- No further relevant information available.

No special measures required.

<u>6 Accidental release measures</u>

 Personal precautions, protective equipment and emergency procedures Environmental precautions: Methods and material for 	Not required. Dilute with much water.
containment and cleaning up	: Dispose of the material collected according to regulations.
• Reference to other sections	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

7 Handling and storage

· Handling

• **Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store (Contd. on page 4)



Page 4/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

	(Contd. of page work clothes separately. Remove soiled, soaked clothin immediately.
 Information about protection against explosions and fires: 	Keep ignition sources away - Do not smoke.
· Conditions for safe storage,	
including any incompatibilities	Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.
· Storage	
· Requirements to be met by	
storerooms and containers: Further information about	Store only in the original container.
storage conditions:	None.
· Storage class	10
[·] Specific end use(s)	No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 107-21-1 Ethanediol

PEL (Malaysia) Ceiling limit: 100 mg/m³, 39.4 ppm

· DNELs

DNEL	S		
CAS:	1344-09-8	Silicic acid, s	sodium salt
Oral	DNE	L 0.8 mg/kg bv	v/Tag (ArL)
Derma	al DNE	L 1.59 mg/kg b	ow/day (ArL)
Inhala	tive DNE	L 5.61 mg/m³ ((ArL)
CAS:	107-21-1	Ethanediol	
Derma	al DNE	L 106 mg/kg b	w/day (ArL)
Inhala	tive DNE	L 35 mg/m³ (A	rL)
· PNEC	s		
CAS:	1344-09-8	Silicic acid, s	sodium salt
PNEC	348 mg/	(Kla)	
	1 mg/l (I	1ew)	
	7.5 mg/l	(Freshwater)	
· Additi	ional info	rmation:	The lists that were valid during the compilation were used as basis. (Contd. on page 5)

_____MY -



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Page 5/10

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

	(Contd. of page 4)
Exposure controls	
Personal protective equip	ment
General protective and	
hygienic measures	Keep away from food, drink and animal feed.
	Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
	Avoid contact with eyes and skin.
Breathing equipment:	Respiratory protection required at insufficiently ventilated
	workplaces and when working with splashes. Fresh air masks or
	combination filters A2-P2 (EN529) are recommended for short-
	term work.
	If applicable, further recommendations for respiratory protection
	can be found in the appendix.
	In case of hypersensitivity of the respiratory tract (asthma, chronic
	bronchitis), handling of the product is not recommended.
Protection of hands:	Suitable materials for protective gloves; EN 374:
	Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).
	Note: suitable materials that provide sufficient protection for
	industrial cleaning with aprotic polar solvents (according to IUPAC
	definition): butyl rubber.
	In case of prolonged or frequently repeated contact, a glove with a
	protection class of 5 or higher is recommended (breakthrough time
	greater than 240 minutes according to EN374). For short-term
	contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes
	according to EN374).
	The thickness of the material is not the only criterion for the level of
	protection of a glove against a chemical substance. The protective
	effect also depends to a large extent on the type of glove material.
	Depending on the type and material, the thickness must be more
	than 0.35 mm to ensure adequate protection in the event of
	prolonged and frequent contact. Exceptions to this rule are multi-
	layer gloves, which guarantee sufficient protection even with a
	thickness of less than 0.35 mm during prolonged wear. Other glove
	materials with a thickness of less than 0.35 mm only provide
	sufficient protection for short periods of wear.
	For solvent-free products:
	Example:
	Polychloroprene - CR: thickness ≥0.5mm; breakthrough time
	≥480min.
	Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time
	<i>≥</i> 480min.
	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.
	Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time
	<i>≥</i> 480min.
	Recommendation: Dispose of contaminated gloves.
Material of gloves	Polychloroprene - CR
	Nitrile rubber - NBR
	Butyl rubber - IIR
	Fluoro rubber - FKM
	(Contd. on page 6)



Page 6/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 5)

Penetration time of glove	
material	Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min.
	Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time ≥480min.
	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: Thickness ≥0.4mm; Breakthrough time ≥480min.
Eye protection: Body protection:	Safety goggles with side protection in accordance with EN 166. Use chemical-resistant protective clothing.
	In case of hypersensitivity of the skin, handling the product is not recommended.

9 Physical and chemical properties

 Information on basic physical and c General Information 	chemical properties
· Appearance: Form:	Fluid
Colour:	Fiula Whitish
· Smell:	Weak, characteristic
· pH-value:	Not determined.
 Change in condition Melting point/freezing point Initial boiling point and boiling rai 	Not determined nge 100 °C
· Flash point:	111 °C
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Steam pressure at 20 °C:	23 hPa
· Density at 20 °C	1.5 g/cm³
 Solubility in / Miscibility with Water: 	Fully miscible
· Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
• Other information	No further relevant information available.

10 Stability and reactivity	

· Reactivity

No further relevant information available.

(Contd. on page 7)

_ м́ү



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Page 7/10

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

		(Contd. of page
	al stability	
	nl decomposition / ons to be avoided:	No decomposition if used according to apositiontions
	ility of hazardous	No decomposition if used according to specifications.
reaction	-	No dangerous reactions known
	ons to avoid	No further relevant information available.
	atible materials:	No further relevant information available.
	ous decomposition	
produc	ts:	No dangerous decomposition products known
Toxico	ological information	on
	ntion on toxicological	effects
Acute t	•	
		vant for classification:
CAS: 1	344-09-8 Silicic acid, s	
Oral	LD50 3400 mg/kg (ra	<i>t</i>)
Dermal	LD50 >5000 mg/kg (r	at)
040.4	07-21-1 Ethanediol	
CAS: 10		
	LD50 4000 mg/kg (ra	<i>t</i>)
	LD50 4000 mg/kg (ra	
Oral	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W	'orkers)
Oral	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r	rorkers) nouse)
Oral Dermal	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r	rorkers) nouse)
Oral Dermal Primary	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r <i>irritant effect:</i>	rorkers) nouse) rabbit)
Oral Dermal Primary Skin co	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r / irritant effect: prosion or irritation	rorkers) nouse)
Oral Dermal Primary Skin co	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye	vorkers) mouse) rabbit) Irritant for skin and mucous membranes.
Oral Dermal Primary Skin co Serious irritatio	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye	rorkers) nouse) rabbit)
Oral Dermal Primary Skin co Serious irritatio Respira sensitiz	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye n atory / skin tation	vorkers) mouse) rabbit) Irritant for skin and mucous membranes.
Oral Dermal Primary Skin co Serious irritatio Respira sensitiz Additio	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye n atory / skin tation nal toxicological	Yorkers) mouse) rabbit) Irritant for skin and mucous membranes. Strong irritant with the danger of severe eye injury. No sensitizing effect known.
Oral Dermal Primary Skin co Serious irritatio Respira sensitiz	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye n atory / skin tation nal toxicological	Yorkers) mouse) rabbit) Irritant for skin and mucous membranes. Strong irritant with the danger of severe eye injury. No sensitizing effect known. The product shows the following dangers according to th
Oral Dermal Primary Skin co Serious irritatio Respira sensitiz Additio	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye n atory / skin tation nal toxicological	Yorkers) mouse) rabbit) Irritant for skin and mucous membranes. Strong irritant with the danger of severe eye injury. No sensitizing effect known. The product shows the following dangers according to th calculation method of the General EC Classification Guidelines fo
Oral Dermal Primary Skin co Serious irritatio Respira sensitiz Additio	LD50 4000 mg/kg (ra LDL0 1600 mg/kg (W LD50 >3500 mg/kg (r 10600 mg/kg (r 10600 mg/kg (r rrosion or irritation s eye damage or eye n atory / skin tation nal toxicological	Yorkers) mouse) rabbit) Irritant for skin and mucous membranes. Strong irritant with the danger of severe eye injury. No sensitizing effect known. The product shows the following dangers according to th

12 Ecological information

· Toxicity · Aquatic toxicity:				
CAS: 1344	4-09-8 Silicic acid, sodium salt			
EC50/72h	>345.4 mg/l (Desmodesmus subspicatus)			
LC50/96h	1108 mg/l (Danio rerio)			
	260 mg/l (Oncorhynchus mykiss)			
	(Contd. on page			

(Contd. on page 8)

⁻ MY



Page 8/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

agent:

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

		(Contd. of page 7	
	>100 mg/l (fish)		
EC50	>100 mg/l (Bak)		
	>100 mg/l (algae)		
	>100 mg/l (Daphnie	en)	
	>100 mg/l (Daphnia	a magna)	
EC50/48h	1700 mg/l (Daphnia magna)		
CAS: 107-	21-1 Ethanediol		
LC50/96h	72860 mg/l (Pimephales promelas)		
EC50/48h	>100 mg/l (Daphnia magna)		
EC50/96h	6500-13000 mg/l (Selenastrum capricornutum)		
NOEC	8590 mg/l (Ceriodaphnia dubia)		
	15380 mg/l (Pimep	hales promelas)	
		ty No further relevant information available.	
	r in environmental		
		No further relevant information available.	
[.] Mobility in soil		No further relevant information available.	
	l ecological inform		
· General notes:		Do not allow undiluted product or large quantities of it to reac ground water, water bodies or sewage system.	
Results of	f PBT and vPvB as	sessment	
PBT:		Not applicable.	
		Not applicable.	
· vPvB:			

13 Disposal information • Waste treatment methods • Recommendation • Must not be disposed of together with household garbage. Do not allow product to reach sewage system. • Uncleaned packagings:

• **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

Water, if necessary with cleaning agent.

· UN-Number		
· ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name		
· ADR, ADN, IMDG, ĬATA	Void	



Page 9/10

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

		(Contd. of page 8
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· Packing group · ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
· Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

CAS: 107-21-1 Ethanediol

· Directive 2012/18/EU

· Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing data specification sheet:	Environment protection department.
Contact:	
Abbreviations and acronyms:	dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)
	PNEC: Predicted No-Effect Concentration (REACH)
	(Contd. on page 10)



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 33

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 9)

Page 10/10

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Irrit. 2: Skin corrosion or irritation – Category 2 Eye Dam. 1: Serious eye damage or eye irritation – Category 1

* Data compared to the previous version altered.

MY -