



BE SURE. BUILD SURE.

Page 1/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40


Revision: 11.04.2025

1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name** **Konudur 250 OM-PL Winterharz - Komponente A**
- **Recommended use of the chemical and restrictions on use**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Synthetic resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazard identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:** Silicic acid, sodium salt
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.
- **Precautionary statements** P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 1)

P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- Chemical characterisation: Mixtures
- Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 1344-09-8	Silicic acid, sodium salt	Eye Dam. 1, H318; Skin Irrit. 2, H315	30-60%
CAS: 107-21-1	Ethanediol	Acute Tox. 4, H302	<5%

- Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.
- After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- After skin contact In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.
- After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
- After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
- Information for doctor
- Most important symptoms and effects, both acute and delayed
Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

(Contd. on page 3)

MY



BE SURE. BUILD SURE.

Page 3/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name **Konudur 250 OM-PL Winterharz - Komponente A**

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed** No information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Dilute with much water.
- **Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

(Contd. on page 4)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 3)

immediately.

· **Information about protection against explosions and fires:** Keep ignition sources away - Do not smoke.

· **Conditions for safe storage, including any incompatibilities** Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· **Storage Requirements to be met by storerooms and containers:** Store only in the original container.

· **Further information about storage conditions:** None.

· **Storage class** 12

· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 107-21-1 Ethanediol

PEL (Malaysia) Ceiling limit: 100 mg/m³, 39.4 ppm

· **DNELs**

CAS: 1344-09-8 Silicic acid, sodium salt

Oral DNEL 0.8 mg/kg bw/Tag (ArL)

Dermal DNEL 1.59 mg/kg bw/day (ArL)

Inhalative DNEL 5.61 mg/m³ (ArL)

CAS: 107-21-1 Ethanediol

Dermal DNEL 106 mg/kg bw/day (ArL)

Inhalative DNEL 35 mg/m³ (ArL)

· **PNECs**

CAS: 1344-09-8 Silicic acid, sodium salt

PNEC 348 mg/l (Kla)

1 mg/l (Mew)

7.5 mg/l (Freshwater)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and**

hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 4)

· Breathing equipment:

Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

· Protection of hands:

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Recommendation: Dispose of contaminated gloves.

· Material of gloves

Polychloroprene - CR

Nitrile rubber - NBR

Butyl rubber - IIR

Fluoro rubber - FKM

· Penetration time of glove material

Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.

(Contd. on page 6)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 5)

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Fluoro rubber - FKM: Thickness $\geq 0.4\text{mm}$; Breakthrough time $\geq 480\text{min}$.

- **Eye protection:**
- **Body protection:**

Safety goggles with side protection in accordance with EN 166.
Use chemical-resistant protective clothing.
In case of hypersensitivity of the skin, handling the product is not recommended.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Whitish
Smell:	Weak, characteristic

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point	Not determined
Initial boiling point and boiling range	100 °C

· **Flash point:** Not applicable

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Steam pressure at 20 °C:** 23 hPa

· **Density** Not determined

· **Solubility in / Miscibility with**

Water: Fully miscible

· **Viscosity:**

dynamic: Not determined.

kinematic: Not determined.

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known

· **Conditions to avoid** No further relevant information available.

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 6)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

CAS: 1344-09-8 Silicic acid, sodium salt

Oral LD50 3400 mg/kg (rat)

Dermal LD50 >5000 mg/kg (rat)

CAS: 107-21-1 Ethanediol

Oral LD50 4000 mg/kg (rat)

LDL0 1600 mg/kg (Workers)

Dermal LD50 >3500 mg/kg (mouse)

10600 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion or irritation** Irritant for skin and mucous membranes.
- **Serious eye damage or eye irritation** Strong irritant with the danger of severe eye injury.
- **Respiratory / skin sensitization** No sensitizing effect known.
- **Additional toxicological information:** The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**

· **Aquatic toxicity:**

CAS: 1344-09-8 Silicic acid, sodium salt

EC50/72h >345.4 mg/l (Desmodesmus subspicatus)

LC50/96h 1108 mg/l (Danio rerio)

260 mg/l (Oncorhynchus mykiss)

>100 mg/l (fish)

EC50 >100 mg/l (Bak)

>100 mg/l (algae)

>100 mg/l (Daphnien)

>100 mg/l (Daphnia magna)

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 7)

EC50/48h	1700 mg/l (Daphnia magna)
CAS: 107-21-1 Ethanediol	
LC50/96h	72860 mg/l (Pimephales promelas)
EC50/48h	>100 mg/l (Daphnia magna)
EC50/96h	6500-13000 mg/l (Selenastrum capricornutum)
NOEC	8590 mg/l (Ceriodaphnia dubia)
	15380 mg/l (Pimephales promelas)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal information

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

14 Transportation information

· UN-Number	
· ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
· ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· ADR, IMDG, IATA	Void

(Contd. on page 9)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 11.04.2025

Version number 40

Revision: 11.04.2025

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 8)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **EHS reference list**

CAS: 107-21-1 | Ethanediol

· **Directive 2012/18/EU**

· **Named dangerous**

substances - ANNEX I None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing data specification sheet:**

Environment protection department.

· **Contact:**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation – Category 1

· *** Data compared to the previous version altered.**