



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name Konudur Flexfit - Komponente A

Recommended use of the chemical and restrictions on

use · Application of the substance

No further relevant information available.

/ the mixture Polyurethane lacquer

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

2 Hazard identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause allergic skin reaction.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

Hazard pictograms



GHS07 GHS08

· Signal word Danger

· Hazard-determining

components of labelling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

crystalline silica

· **Hazard statements** H317 May cause allergic skin reaction.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements** P260 Do not breathe dust/fume/gas/mist/ vapours/spray.

(Contd. on page 2)



Page 2/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 1)

P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

· Other hazards

Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

· **Description:** Resin mixture.

Mixture consisting of the following components.

· Dangerous components:			
CAS: 136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	30-60%	
	Skin Sens. 1, H317; Aquatic Chronic 3, H412		
CAS: 14808-60-7	crystalline silica	10-30%	
	STOT RE 1, H372		

4 First-aid measures

· Description of first aid measures

General information Remove soiled, soaked clothing immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· Information for doctor

· Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

· Indication of any immediate medical attention and special

treatment needed Therapeutic measures: No information available.

MY



Page 3/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

• Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Not required.

· Environmental precautions: No special measures required.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

• **Reference to other sections** No dangerous materials are released.

7 Handling and storage

Handling

· Precautions for safe handling Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

(Contd. on page 4)



Page 4/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 3)

· Conditions for safe storage,

including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

Requirements to be met by

storerooms and containers: Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

· Further information about

storage conditions: Keep container tightly closed in a well-ventilated place.

· Storage class 6.1

· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 14808-60-7 crystalline silica

PEL (Malaysia) Long-term value: 0.1* mg/m³

*Pecahan ternafaskan

· DNELs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal DNEL 4 mg/kg bw/day (ArL)
Inhalative DNEL 28 mg/m³ (ArL)
112 mg/m³ (Ark)

PNECs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC 31.1 mg/l (Kla)

0.000013 mg/l (Mew)

0.00013 mg/l (Freshwater)

PNEC 0.1 mg/kg dwt (Bod)

0.02 mg/kg dwt (Marine water sediment)

0.21 mg/kg dwt (Fresh water sediment)

(Contd. on page 5)



Page 5/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 4)

• Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Do not smoke, eat or drink while working. Have eye wash

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and

skin.

Do not store food in the work area. Wash hands before breaks and

at the end of work.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

An nicht ausreichend entlüfteten Arbeitsplätzen und bei Spritzverarbeitung Atemschutz erforderlich. Empfohlen werden Frischluftmaske oder für kurzzeitige Arbeiten Kombinationsfilter

A2-P2.

Bei Überempfindlichkeit der Atemwege und der Haut (Asthma, chronische Bronchitis, chronische Hautleiden) wird der Umgang

mit dem Produkt abgeraten.

• **Protection of hands:** Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness \ge 0.5mm; breakthrough time \ge 480min. Fluororubber - FKM: thickness \ge 0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

Recommendation: Dispose of contaminated gloves.

Bedingt geeignete Materialien für Schutzhandschuhe; EN 374-3:

Nitrilkautschuk - NBR: Dicke ≥0,35mm

Nur als Spritzschutz geeignet. Nur bei kurzzeitiger Einwirkung geeignet. Bei Kontamination sind die Schutzhandschuhe sofort zu

wechseln.

· Material of gloves The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

· Penetration time of glove

material

Butyl rubber - IIR: thickness \geq 0.5mm; breakthrough time \geq 480min. Fluoro rubber - FKM: thickness \geq 0.4mm; breakthrough time

>480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

· Eye protection:

Wear safety goggles/face protection.

Body protection: Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.



Page 6/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 5)

Information on basic physical and c	hemical properties
General Information	member properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
Smell:	Characteristic
pH-value:	Not determined.
Change in condition	
Melting point/freezing point	Not determined
Initial boiling point and boiling rar	nge 185 °C
Flash point:	100 °C
Auto-ignition temperature	350 °C
Auto-ignition temperature	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Steam pressure at 20 °C:	2 hPa
Density at 20 °C	1.99 g/cm³
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Viscosity:	
dynamic:	Not determined.

10 Stability and reactivity

• Reactivity No further relevant information available.

· Chemical stability

 Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous

reactions No dangerous reactions known

• Conditions to avoid No further relevant information available. Incompatible materials: No further relevant information available.

· Hazardous decomposition products:

No dangerous decomposition products known

MY



Page 7/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values that are relevant for classification:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)
Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

Primary irritant effect:

Serious eye damage or eye

irritation No irritant effect.

Respiratory / skin

sensitization Sensitization possible by skin contact.

· Additional toxicological

information: The product shows the following dangers according to the

calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Irritant

12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h 66 mg/l (Danio rerio) (OECD 203)

EC50 3110 mg/l (BEL)

EC50/48h 88.6 mg/l (Daphnia magna) NOEC 0.01 mg/l (Daphnia magna)

ErC50/72h 113 mg/l (Scenedesmus subspicatus)

· Persistence and degradability No further relevant information available.

· Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

• Other adverse effects No further relevant information available.

MY



Page 8/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 7)

13 Disposal information

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14 Transportation information

· UN-Number · ADR, ADN, IMDG, IATA	Void		
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void		
· Transport hazard class(es)			
· ADR, ADN, IMDG, IATA · Class	Void		
· Packing group · ADR, IMDG, IATA	Void		
· Environmental hazards: · Marine pollutant:	No		
· Special precautions for user	Not applicable.		
Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.			
· UN "Model Regulation":	Void		

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · EHS reference list

CAS: 136210-30-5 | tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

- · Directive 2012/18/EU
- · Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

MY -



Page 9/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024 Version number 37 Revision: 10.12.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 8)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Sens. 1: Skin sensitization - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard -

Category 3

· * Data compared to the previous version altered.