

Page 1/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name Konudur Robopox 10 - Komponente A

· Recommended use of the chemical and restrictions on

No further relevant information available.

· Application of the substance Epoxy resin / the mixture

· Details of the supplier of the safety data sheet

MC-Bauchemie Müller GmbH & Co. KG · Manufacturer/Supplier:

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

2 Hazard identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· Label elements

· GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms





GHS07 GHS09

· Signal word Warning

· Hazard-determining

components of labelling:

4,4'-Methylenediphenyldiglycidyl ether

Benzvl alcohol

Hydrophobes Siliziumdioxid, synthetisch, amorph

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}

methyl)oxirane

(Contd. on page 2)



(Contd. of page 1)



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

• Precautionary statements P261 Avoid breathing dust/fume/ gas/mist/vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362 Take off contaminated clothing and wash before

reuse.

P363 Wash contaminated clothing before reuse.

· Other hazards

· Hazard statements

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

Description: Mixture consisting of the following components.

oonents:	
Calcium carbonate	30-60%
4,4'-Methylenediphenyldiglycidyl ether	<i>≥</i> 25- <i>≤</i> 30%
Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Benzyl alcohol	<2.5%
Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≥1-<2.5%
Eye Dam. 1, H318	
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane	≥1-<2.5%
Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
Hydrophobes Siliziumdioxid, synthetisch, amorph	<2.5%
Acute Tox. 4, H302	
Phenol, reaction products with divinylbenzene	<1.5%
Aquatic Chronic 3, H412	
decarboxylating cashew nut shell liquid	≥0.1-<1%
Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	
	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 Hydrophobes Siliziumdioxid, synthetisch, amorph Acute Tox. 4, H302 Phenol, reaction products with divinylbenzene Aquatic Chronic 3, H412



Page 3/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

CAS: 13463-67-7 | Titanium dioxide (Contd. of page 2)

Carc. 2, H351

• Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

• After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· Information for doctor

· Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture No further relevant information available.

· Advice for firefighters

• **Protective equipment:** No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and

emergency procedures Not required.

· Environmental precautions: Inform respective authorities in case product reaches water or

sewage system.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 3)

See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· Conditions for safe storage, including any incompatibilities

·Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.
Storage class 10

8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 1317-65-3 Calcium carbonate

PEL (Malaysia) Long-term value: 10 mg/m³

· DNELs

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

CAS: 100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

(Contd. on page 5)



Page 5/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 4)

Dermal DNEL 8 mg/kg bw/day (Ark)
40 mg/kg bw/day (Ark)
Inhalative DNEL 22 mg/m³ (ArL)
110 mg/m³ (Ark)

· PNECs

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

CAS: 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

· Additional information:

The lists that were valid during the compilation were used as basis.

- · Exposure controls
- · Personal protective equipment
- · General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

• **Protection of hands:** Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

• Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

(Contd. on page 6)





Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

· Penetration time of glove

· Body protection:

(Contd. of page 5)

material The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety googles

Eye protection: Tight-fitting safety goggles.

Safety goggles.

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

9 Physical and chemical properties

· Information on basic physical and · General Information	chemical properties	
· Appearance:	Death	
Form:	Pasty	
Colour:	grayish	
· Smell:	Characteristic	
· pH-value:	Not applicable. Not determined.	
Observe to a solition	Not determined.	
Change in condition	Alak daka wasin a d	
Melting point/freezing point	Not determined	
Initial boiling point and boiling ra	inge >320 °C	
· Flash point:	>61 °C	

455 °C

Product is not explosive.

Product is not selfigniting.

· Steam pressure at 25 °C: 0 hPa

· Auto-ignition temperature

· Ignition temperature:

· Explosive properties:

· Density at 20 °C 1.75 g/cm³

(Contd. on page 7)





Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 6)

· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
· Viscosity:		
dynamic at 20 °C:	400000 mPas	
kinematic:	Not determined.	
· Other information	No further relevant information available.	

10 Stability and reactivity

• Reactivity No further relevant information available.

Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous

reactions

No dangerous reactions known

· Conditions to avoid · Incompatible materials:

No further relevant information available. No further relevant information available.

· Hazardous decomposition

products: No dangerous decomposition products known

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

CAS: 131	7-65-3 Calcium carbona	ate	
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
CAS: 167	5-54-3 4,4'-Methylenedi	phenyldiglycidyl ether	
Oral	LD50	11400 mg/kg (rat)	
Dermal	LD50	23000 mg/kg (rabbit)	
		>2000 mg/kg (rat)	
CAS: 100	-51-6 Benzyl alcohol		
Oral	LD50	1230 mg/kg (rat)	
	NOAEL 2nd year study	200 mg/kg (mouse)	
		200 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4178 mg/l (rat)	
CAS: 253	0-83-8 [3-(2,3-epoxypro	poxy)propyl]trimethoxysilane	
Oral	LD50	8030 mg/kg (rat)	





Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

		(Contd. of page 7)
Dermal	LD50	4248 mg/kg (rabbit)
CAS: 900	bis(oxirane) a	s of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] nd 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] d 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 677	62-90-7 Hydrophobes S	Siliziumdioxid, synthetisch, amorph
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 932	81-16-4 Phenol, reactio	n products with divinylbenzene
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)
CAS: 134	63-67-7 Titanium dioxid	le
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

Primary irritant effect:

Skin corrosion or irritation

· Serious eye damage or eye

irritation

· Respiratory / skin

sensitization

· Additional toxicological

information:

Irritant for skin and mucous membranes.

No irritant effect.

No sensitizing effect known.

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Irritant

12 Ecological information

· Toxicity

· Aquatic toxic	city:	
CAS: 1317-6	5-3 Calciun	n carbonate
	EC50/72h	>14 mg/l (Desmodesmus subspicatus)
	LC50/96h	>10000 mg/l (Oncorhynchus mykiss)
	LC50/48h	>1000 mg/l (Daphnia magna)
	EC50/48h	>1000 mg/l (Daphnia magna)
CAS: 1675-5	4-3 4,4'-Met	hylenediphenyldiglycidyl ether
	LC50/72h	>11 mg/l (algae)
	IC50	>42.6 mg/l (Bak)
	LC50/96h	2 mg/l (Oncorhynchus mykiss)
		(Contd. on page 0)

(Contd. on page 9)



Page 9/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

		(Contd. of page 8)
		1.3 mg/l (fish)
	EC50/48h	2.1 mg/l (daphnia)
		1.8 mg/l (Daphnia magna)
	ErC50/72h	11 mg/l (Selenastrum capricornutum)
CAS: 100-51	-6 Benzyl a	lcohol
	IC50/72h	700 mg/l (algae)
	LC50/96h	460 mg/l (Pimephales promelas)
		10 mg/l (Lepomis macrochirus)
CAS: 2530-8	3-8 [3-(2,3-e	epoxypropoxy)propyl]trimethoxysilane
	LC50/96h	55 mg/l (Cyp)
	EC50/48h	473 mg/l (Daphnia magna)
	ErC50/72h	255 mg/l (Scenedesmus subspicatus)
CAS: 9003-3	bis(oxi	on mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] irane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] rane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
	LC50/96h	>100 mg/l (Daphnia magna)
	EC50/96h	>100 mg/l (Leucidus idus)
CAS: 67762-	90-7 Hydroj	phobes Siliziumdioxid, synthetisch, amorph
Sensitisation	EL50	10000 mg/l (Daphnien)
	LC50/96h	>10000 mg/l (Brachydanio rerio)
		ı

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

• General notes: Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

· Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 10)



Page 10/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 9)

· Uncleaned packagings:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Recommendation:

LIQUID, N.O.S. (Epoxide resin) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Epoxide resin), MARIN POLLUTANT 9 (M6) Miscellaneous dangerous substances al articles. 9
LIQUID, N.O.S. (Epoxide resin) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Epoxide resin), MARIN POLLUTANT 9 (M6) Miscellaneous dangerous substances at articles. 9 9 Miscellaneous dangerous substances and articles 9
ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Epoxide resin), MARIN POLLUTANT 9 (M6) Miscellaneous dangerous substances at articles. 9 9 Miscellaneous dangerous substances and articles and articles. 9
ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Epoxide resin), MARIN POLLUTANT 9 (M6) Miscellaneous dangerous substances at articles. 9 9 Miscellaneous dangerous substances and articles. 9
POLLUTANT 9 (M6) Miscellaneous dangerous substances an articles. 9 9 Miscellaneous dangerous substances and articles. 9
9 (M6) Miscellaneous dangerous substances at articles. 9 9 Miscellaneous dangerous substances and articles. 9
articles. 9 9 Miscellaneous dangerous substances and articles 9
articles. 9 9 Miscellaneous dangerous substances and articles 9
articles. 9 9 Miscellaneous dangerous substances and articles 9
9 9 Miscellaneous dangerous substances and articles 9
9 Miscellaneous dangerous substances and articles 9
9
9
III
III
Yes
Symbol (fish and tree) Symbol (fish and tree)
Symbol (fish and tree)
Warning: Miscellaneous dangerous substances a
articles.
90
F-A,S-F
A
of Not applicable.
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml



Page 11/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 14.04.2025 Version number 44 Revision: 14.04.2025

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 10)

· Transport category 3 · Tunnel restriction code (-)

· IMDG

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN), 9,

III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS: 100-51-6 Benzyl alcohol

· Directive 2012/18/EU · Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)



Page 12/12

Safety Data Sheet according to P.U.(A) 310/2013

Revision: 14.04.2025 Printing date 14.04.2025 Version number 44

Trade name Konudur Robopox 10 - Komponente A

(Contd. of page 11)

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4 Skin Irrit. 2: Skin corrosion or irritation - Category 2

Eye Dam. 1: Serious eye damage or eye irritation - Category 1 Eye Irrit. 2: Serious eye damage or eye irritation – Category 2

Skin Sens. 1: Skin sensitization – Category 1

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard -

Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard — Category 3

· * Data compared to the previous version altered.