



BE SURE. BUILD SURE.

Page 1/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79




Revision: 06.12.2024

1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name** MC-DUR 1200 VK - Komponente A
- **Recommended use of the chemical and restrictions on use** No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
Epoxy impregnation
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazard identification

- **Classification of the substance or mixture**
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause allergic skin reaction.
 - Repr. 1B H360 May damage fertility or the unborn child.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS07 GHS08 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:** epoxide derivates
Alkyl Glycidyl Ether
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}
oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]
dioxirane

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

Safety Data Sheet
according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 1)

· Hazard statements	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause allergic skin reaction. H360 May damage fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects.
· Precautionary statements	P261 Avoid breathing dust/fume/ gas/mist/vapours/ spray. P280 Wear protective gloves / eye protection / face protection. P281 Use personal protective equipment as required. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse.
· Other hazards	
· Results of PBT and vPvB assessment	
· PBT:	Not applicable.
· vPvB:	Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- **Chemical characterisation: Mixtures**
- **Description:** Resin mixture with colouring agents.
Mixture consisting of the following components.

· Dangerous components:

CAS: 1675-54-3	epoxide derivatives Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-80%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<10%
CAS: 9003-36-5	Reaction mass of 2, 2'-[methylenebis(4, 1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2, 2'-[methylenebis(2, 1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 68609-97-2	Alkyl Glycidyl Ether Repr. 1B, H360; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<5%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%

(Contd. on page 3)

MY



BE SURE. BUILD SURE.

Page 3/12

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

· Additional information

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

· After inhalation

Supply fresh air; seek medical advice if symptoms occur.

· After skin contact

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· After eye contact

Rinse opened eye for several minutes under running water. Call a doctor immediately

· After swallowing

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· Information for doctor

· Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable extinguishing agents

Water with a full water jet.

· Special hazards arising from the substance or mixture

No further relevant information available.

· Advice for firefighters

· Protective equipment:

Wear self-contained breathing apparatus.

· Additional information

Cool endangered containers with water spray jet.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case product reaches water or sewage system.

Prevent material from reaching sewage system, holes and cellars.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 3)

- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** None.
- **Storage class** 6.1C

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL)
------	------	----------------------

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 4)

Dermal	DNEL	20 mg/kg bw/Tag (Ark)
		8 mg/kg bw/day (ArL)
Inhalative	DNEL	40 mg/kg bw/day (Ark)
		22 mg/m ³ (ArL)
		110 mg/m ³ (Ark)

CAS: 68609-97-2 Alkyl Glycidyl Ether

Dermal	DNEL	0.75 mg/kg bw/day (ArL)
Inhalative	DNEL	0.49 mg/m ³ (ArL)

· PNECs

CAS: 100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

CAS: 68609-97-2 Alkyl Glycidyl Ether

PNEC	0.00072 mg/l (Mew)
	0.0072 mg/l (Freshwater)
PNEC	80.12 mg/kg dwt (Bod)
	6.677 mg/kg dwt (Sediment)
	66.77 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".
The selection of a suitable glove depends not only on the material,

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 5)

but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· Eye protection:

Tight-fitting safety goggles.

Safety goggles.

· Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: Light yellow

· Smell: Characteristic

· pH-value: Not determined.

· Change in condition

Melting point/freezing point Not determined

Initial boiling point and boiling range >200 °C

· Flash point: 101 °C

· Auto-ignition temperature 184 °C

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety Data Sheet
according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 6)

· Auto-ignition temperature	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· Critical values for explosion:	
Lower:	1.3 Vol %
Upper:	13 Vol %
· Steam pressure at 20 °C:	0.1 hPa
· Density at 20 °C	1.14 g/cm ³
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Viscosity:	
dynamic at 20 °C:	820 mPas
kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity	No further relevant information available.
· Possibility of hazardous reactions	No dangerous reactions known
· Conditions to avoid	No further relevant information available.
· Incompatible materials:	No further relevant information available.
· Hazardous decomposition products:	Possible in traces.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 epoxide derivates

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

(Contd. on page 8)

MY



BE SURE. BUILD SURE.

Page 8/12

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 7)

Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 68609-97-2 Alkyl Glycidyl Ether		
Oral	LD50	17100 mg/kg (rat)

- **Primary irritant effect:**

- **Skin corrosion or irritation** Irritant for skin and mucous membranes.

- **Serious eye damage or eye irritation** No irritant effect.

- **Respiratory / skin sensitization** No sensitizing effect known.

- **Additional toxicological information:** The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)** Repr. 1B

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

CAS: 1675-54-3 epoxide derivatives	
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
CAS: 100-51-6 Benzyl alcohol	
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)
CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

(Contd. on page 9)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 8)

CAS: 68609-97-2 Alkyl Glycidyl Ether

EbC50/72h 843 mg/l (*Pseudokirchneriella subcapitata*)

LC50/96h >5000 mg/l (*Oncorhynchus mykiss*)

1800 mg/l (*Lepomis macrochirus*)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (*Pseudokirchneriella subcapitata*)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal information

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transportation information

- **UN-Number**
- **ADR, IMDG, IATA** UN3082
- **UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates), MARINE POLLUTANT

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 9)

· Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· Packing group	
· ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A, S-F
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· Remarks:	1 kg Gebinde: Begrenzte Mengen
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

MY

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 10)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **EHS reference list**

CAS: 1675-54-3	epoxide derivates
CAS: 100-51-6	Benzyl alcohol
CAS: 68609-97-2	Alkyl Glycidyl Ether

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

- **Seveso category**

E2 Hazardous to the Aquatic Environment

- **Qualifying quantity (tonnes) for the application of lower-tier requirements**

200 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements**

500 t

- **National regulations**

0.67 %

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:**

Environment protection department.

- **Contact:**

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity - oral – Category 4
 Skin Irrit. 2: Skin corrosion or irritation – Category 2
 Eye Irrit. 2: Serious eye damage or eye irritation – Category 2
 Skin Sens. 1: Skin sensitization – Category 1

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety Data Sheet
according to P.U.(A) 310/2013

Printing date 10.12.2024

Version number 79

Revision: 06.12.2024

Trade name MC-DUR 1200 VK - Komponente A

(Contd. of page 11)

Repr. 1B: Reproductive toxicity – Category 1B

Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard – Category 3

**· * Data compared to the
previous version altered.**

MY