



BE SURE. BUILD SURE.

Page 1/12

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025


Version number 52

Revision: 12.04.2025

### 1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name** **MC-DUR 1365 HBF - Komponente B**
- **Recommended use of the chemical and restrictions on use** *No further relevant information available.*
- **Application of the substance / the mixture** *Epoxy coating  
Hardening agent/ Curing agent*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** *MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de*  
*MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533*
- **Informing department:** *msds@mc-bauchemie.de*

### 2 Hazard identification

- **Classification of the substance or mixture**
  - Skin Corr. 1 H314 Causes severe skin burns and eye damage.*
  - Eye Dam. 1 H318 Causes serious eye damage.*
  - Skin Sens. 1 H317 May cause allergic skin reaction.*
  - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.*
- **Label elements**
- **GHS label elements** *The product is classified and labelled according to the Globally Harmonised System (GHS).*
- **Hazard pictograms**  
  
GHS05 GHS07 GHS09
- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
  - 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine*
  - Isophorone diamine*
  - 2-Propennitril, Polymer mit 1,3-Butadien, 1-Cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert*
  - 2,4,6-Tri-(dimethylaminomethyl)phenol*
  - 2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid*

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 1)

- **Hazard statements**
  - H314 Causes severe skin burns and eye damage.
  - H317 May cause allergic skin reaction.
  - H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
  - P260 Do not breathe dusts or mists.
  - P261 Avoid breathing dust/fume/ gas/mist/vapours/ spray.
  - P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P310 Immediately call a POISON CENTER/doctor.
  - P321 Specific treatment (see on this label).
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and information of the ingredients of the hazardous chemical

- **Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	10-30%
CAS: 68683-29-4	2-Propennitril, Polymer mit 1,3-Butadien, 1-Cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert Skin Irrit. 2, H315; Skin Sens. 1, H317	10-30%
CAS: 90-72-2	2,4,6-Tri-(dimethylaminomethyl)phenol Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥5-<10%
CAS: 2855-13-2	Isophorone diamine Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
CAS: 61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<3%
CAS: 25620-58-0	trimethylhexane-1,6-diamine Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.1-<1%

(Contd. on page 3)

MY



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 2)

CAS: 61788-46-3	Amines, coco alkyl STOT RE 2, H373; Asp. Haz., H304; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; STOT SE 3, H335	≥0.25-<1%
CAS: 140-31-8	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

- **Description of first aid measures**
- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/12

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 3)

- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### 7 Handling and storage

- **Handling**
- **Precautions for safe handling** Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Storage class** 8A

### 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

MY



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 4)

**· DNELs**

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Inhalative DNEL 0.31 mg/m<sup>3</sup> (ArL)

**CAS: 2855-13-2 Isophorone diamine**

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m<sup>3</sup> (ArL)

**CAS: 140-31-8 2-piperazin-1-ylethylamine**

Dermal DNEL 3.33 mg/kg bw/day (ArL)

Inhalative DNEL 10.6 mg/m<sup>3</sup> (ArL)

**· PNECs**

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

PNEC 72 mg/l (Sewage Treatment Plant)

0.102 mg/l (Fresh water)

0.01 mg/l (Mew)

PNEC 10 mg/kg dwt (Bod)

0.062 mg/kg dwt (Sediment)

0.622 mg/kg dwt (Fresh water sediment)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

PNEC 0.2 mg/l (Sewage Treatment Plant)

0.0084 mg/l (Mew)

0.084 mg/l (Freshwater)

**CAS: 2855-13-2 Isophorone diamine**

PNEC 0.006 mg/l (Mew)

0.06 mg/l (Freshwater)

PNEC 0.578 mg/kg dwt (Sediment)

5.784 mg/kg dwt (Fresh water sediment)

**CAS: 140-31-8 2-piperazin-1-ylethylamine**

PNEC 250 mg/l (Kla)

0.0058 mg/l (Mew)

0.058 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

21.5 mg/kg dwt (Sediment)

215 mg/kg dwt (Fresh water sediment)

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· Exposure controls**

**· Personal protective equipment**

**· General protective and  
hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

(Contd. on page 6)



BE SURE. BUILD SURE.

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 5)

- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Protection of hands:** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
Nitrile rubber  
Recommended material thickness:  $\geq 0.4$  mm*
- **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.  
The following applies to all other gloves:  
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.  
Nitrile rubber  
Material thickness:  $\geq 0.40$  mm  
Penetration time:  $\geq 480$  min  
Butyl rubber:  
Material thickness:  $\geq 0.5$  mm  
Penetration time:  $\geq 480$  min*
- **Eye protection:** *Tight-fitting safety goggles.  
Safety goggles.*
- **Body protection:** *Protective clothing  
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.*

MY

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

Trade name MC-DUR 1365 HBF - Komponente B

(Contd. of page 6)

#### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Viscous
· <b>Colour:</b>	Whitish
· <b>Smell:</b>	Characteristic

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/freezing point</b>	Not determined
· <b>Initial boiling point and boiling range</b>	Not determined

· **Flash point:** >100 °C

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Steam pressure:** Not determined.

· **Density at 20 °C** 1.15 g/cm<sup>3</sup>

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix

· **Viscosity:**

· <b>dynamic at 20 °C:</b>	60000 mPas
· <b>kinematic:</b>	Not determined.

· **Other information** No further relevant information available.

#### 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions**

No dangerous reactions known

· **Conditions to avoid**

No further relevant information available.

· **Incompatible materials:**

No further relevant information available.

· **Hazardous decomposition products:**

No dangerous decomposition products known

MY

(Contd. on page 8)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

Trade name MC-DUR 1365 HBF - Komponente B

(Contd. of page 7)

## 11 Toxicological information

- Information on toxicological effects
- Acute toxicity

· LD/LC50 values that are relevant for classification:

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

Oral	LD50	910 mg/kg (rat)
	NOAEL	10 mg/kg (rat)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

**CAS: 2855-13-2 Isophorone diamine**

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)
		1840 mg/kg (rabbit)

**CAS: 25620-58-0 trimethylhexane-1,6-diamine**

Oral	LD50	910 mg/kg (rat)
------	------	-----------------

**CAS: 140-31-8 2-piperazin-1-ylethylamine**

Oral	LD50	2000-5000 mg/kg (rat)
		500 mg/kg (rabbit)
Dermal	LD50	200-1000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion or irritation Caustic effect on skin and mucous membranes.

· Serious eye damage or eye irritation Irritant effect.

· Respiratory / skin sensitization Sensitization possible by skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Harmful  
Corrosive  
Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

MY

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety Data Sheet**  
according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 8)

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:**

**CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine**

EC50/24h	31.5 mg/l (Daphnien)
EC50	89 mg/l (Pseudomonas putida)
LC50/48h	174 mg/l (Leucidus idus)
NOEC	10.9 mg/l (Danio rerio)
	16 mg/l (Pseudokirchneriella subcapitata)
	1.02 mg/l (Daphnia magna)
ErC50/72h	43.5 mg/l (Pseudokirchneriella subcapitata)

**CAS: 90-72-2 2,4,6-Tri-(dimethylaminomethyl)phenol**

EC50/72h	84 mg/l (Desmodesmus subspicatus)
LC50/96h	175 mg/l (Cyp)
	718 mg/l (Daphnia magna)
NOEC	2 mg/l (BEL)
	6.25 mg/l (Desmodesmus subspicatus)

**CAS: 2855-13-2 Isophorone diamine**

LC50/96h	110 mg/l (fish)
	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (daphnia)
	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)
	>50 mg/l (algae)

**CAS: 25620-58-0 trimethylhexane-1,6-diamine**

LC50/96h	31.5 mg/l (Daphnies)
----------	----------------------

**CAS: 140-31-8 2-piperazin-1-ylethylamine**

EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Danger to drinking water if even extremely small quantities leak into soil.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

Trade name MC-DUR 1365 HBF - Komponente B

(Contd. of page 9)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

#### 13 Disposal information

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### 14 Transportation information

- **UN-Number**
- **ADR, IMDG, IATA** UN2735
- **UN proper shipping name**
- **ADR** AMINES, LIQUID, CORROSIVE, N.O.S. (TRIMETHYLHEXAMETHYLENEDIAMINES, 2,4,6-Tri-(dimethylaminomethyl)phenol), ENVIRONMENTALLY HAZARDOUS
- **IMDG** AMINES, LIQUID, CORROSIVE, N.O.S. (TRIMETHYLHEXAMETHYLENEDIAMINES, 2,4,6-Tri-(dimethylaminomethyl)phenol), MARINE POLLUTANT
- **IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (TRIMETHYLHEXAMETHYLENEDIAMINES, 2,4,6-Tri-(dimethylaminomethyl)phenol)
- **Transport hazard class(es)**
- **ADR**
- **Class** 8 (C7) Corrosive substances.
- **Label** 8
- **IMDG, IATA**
- **Class** 8 Corrosive substances.
- **Label** 8
- **Packing group**
- **ADR, IMDG, IATA** III
- **Environmental hazards:** Product contains environmentally hazardous substances: 2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid
- **Marine pollutant:** Yes  
Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)

(Contd. on page 11)



BE SURE. BUILD SURE.

**Safety Data Sheet**  
according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 10)

<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Kemler Number:</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Segregation groups</b></li> <li>· <b>Stowage Category</b></li> <li>· <b>Segregation Code</b></li> </ul>	<p>Warning: Corrosive substances.</p> <p>80</p> <p>F-A, S-B</p> <p>(SGG18) Alkalis</p> <p>A</p> <p>SG35 Stow "separated from" SGG1-acids</p>
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	<p>Not applicable.</p>
<p>· <b>Transport/Additional information:</b></p>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p> <p>3</p> <p>E</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (TRIMETHYLHEXAMETHYLENEDIAMINES, 2,4,6-TRI-(DIMETHYLAMINOMETHYL)PHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS</p>

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **EHS reference list**

CAS: 90-72-2	2,4,6-Tri-(dimethylaminomethyl)phenol
CAS: 2855-13-2	Isophorone diamine
CAS: 61788-46-3	Amines, coco alkyl
CAS: 140-31-8	2-piperazin-1-ylethylamine

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

· **Seveso category**

None of the ingredients is listed.

E2 Hazardous to the Aquatic Environment

(Contd. on page 12)

MY



BE SURE. BUILD SURE.

Page 12/12

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 52

Revision: 12.04.2025

**Trade name MC-DUR 1365 HBF - Komponente B**

(Contd. of page 11)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing data specification sheet:** Environment protection department.
- **Contact:**
- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 4: Acute toxicity - oral – Category 4  
Acute Tox. 3: Acute toxicity - oral – Category 3  
Skin Corr. 1: Skin corrosion or irritation – Category 1  
Skin Irrit. 2: Skin corrosion or irritation – Category 2  
Eye Dam. 1: Serious eye damage or eye irritation – Category 1  
Skin Sens. 1: Skin sensitization – Category 1  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Haz.: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - chronic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard – Category 3
- **\* Data compared to the previous version altered.**

MY