

Page 1/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name MC-Fast RC

Recommended use of the chemical and restrictions on

use

No further relevant information available.

· Application of the substance

/ the mixture Regulated set cement

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

Emergency telephone

msds@mc-bauchemie.de

number: Abteilung Produktsicherheit

2 Hazard identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms





GHS05 GHS07

· Signal word Danger

· Hazard-determining

components of labelling: Portland cement (low chromate)

calcium oxide

· Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 1)

· Precautionary statements P261 Avoid breathing dust/fume/ gas/mist/vapours/

sprav.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous comp	ponents:	
	Portland cement (low chromate)	50-70%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 14808-60-7	Quartz sand	10-30%
CAS: 1305-78-8	calcium oxide	≥3-<5%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 1317-65-3	Calcium carbonate	<2.5%
CAS: 497-19-8	Sodium carbonate	<2.5%
	Eye Irrit. 2, H319	

· Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information For all first aid measures: observe self-protection and consult a

doctor!

· After inhalation Remove people from the dusty area.

After skin contact Remove heavily soiled clothing. Clean with plenty of soap and

water.

· After eye contact Rinse for 10 minutes under running water with the eyelids open.

Always consult an ophthalmologist!

• After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

- MY



Page 3/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

• Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Not required.

· Environmental precautions: No special measures required.

Methods and material for

containment and cleaning up: Collect mechanically.

· Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling Avoid dust formation! Avoid spraying the ready-to-use cementitious

product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and

after each break. Observe work restrictions!

· Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: Store bags tightly closed; protect from moisture and water!

Store containers tightly closed in a well-ventilated and well-lit room.

Access only for specialised personnel.

Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages,

passageways and confined spaces.

· Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

kg.

Do not store together with substances of the following LGK: 1; 6.2;

7

Storage with substances of the following LGK is only possible

under the conditions specified in TRGS 510: 4.1A; 5.1C

(Contd. on page 4)



Page 4/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 3)

· Further information about

storage conditions: Store in a dry and frost-free place.

· Storage class 13

8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 65997-15-1 Portland cement (low chromate)

PEL (Malaysia) Long-term value: 10 mg/m³

CAS: 14808-60-7 Quartz sand

PEL (Malaysia) Long-term value: 0.1* mg/m³

*Pecahan ternafaskan

CAS: 1305-78-8 calcium oxide

PEL (Malaysia) Long-term value: 2 mg/m³

CAS: 1317-65-3 Calcium carbonate

PEL (Malaysia) Long-term value: 10 mg/m³

· DNELs

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1305-78-8 calcium oxide

Inhalative DNEL 1 mg/m³ (ArL)

minatative DNLL Ting/iii (AIL)

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

CAS: 497-19-8 Sodium carbonate

Inhalative DNEL 10 mg/m³ (ArL)

· PNECs

CAS: 1305-78-8 calcium oxide

PNEC 2.27 mg/l (BEL)

0.24 mg/l (Mew)

0.37 mg/l (Freshwater)

PNEC 817.4 mg/kg dwt (Bod)

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

• Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)

ΜY



Page 5/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 4)

· Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks!

Use skin care products after work (moisturising cream).

Change and clean heavily soiled clothing! Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and

after every break.

· Breathing equipment: For work with higher dust loads particle filter class P2

• Protection of hands: Check protective gloves prior to each use for their proper condition.

• Material of gloves Nitrile impregnated cotton gloves.

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

• Eye protection: Safety glasses

· Body protection: Protective work clothing.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder Colour: Grey
Smell: Odourless

· **pH-value:** Not applicable.

· Change in condition

Melting point/freezing point Not determined

Initial boiling point and boiling range 2230 °C

· Flash point: Not applicable

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive.

13.5 hPa

· Density at 20 °C 2.98 g/cm³

· Solubility in / Miscibility with

· Steam pressure at 1732 °C:

Water: Unsoluble

· Viscosity:

dynamic: Not applicable.
kinematic: Not applicable.

(Contd. on page 6)



Page 6/9

Safety Data Sheet according to P.U.(A) 310/2013

Version number 35 Revision: 12.04.2025 Printing date 12.04.2025

Trade name MC-Fast RC

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

Reactivity

No further relevant information available.

· Chemical stability

Thermal decomposition /

conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous

reactions

No dangerous reactions known

· Conditions to avoid · Incompatible materials:

No further relevant information available. No further relevant information available.

· Hazardous decomposition

products:

No dangerous decomposition products known

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity

710010101				
· LD/LC50	values tha	t are relevant for classification:		
CAS: 659	97-15-1 Pc	ortland cement (low chromate)		
Dermal	LD50	2000 mg/kg (rabbit)		
Inhalative	LC50/4 h	5 mg/l (rat)		
CAS: 130	CAS: 1305-78-8 calcium oxide			
Oral	LD50	>2000 mg/kg (rat)		
Dermal	LD50	>2500 mg/kg (rabbit)		
CAS: 131	CAS: 1317-65-3 Calcium carbonate			
Oral	LD50	>2000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
CAS: 497	-19-8 Sodi	um carbonate		
Oral	LD50	2800 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rabbit)		
Inhalative	LC50/4 h	2.3 mg/l (rat)		

Primary irritant effect:

Skin corrosion or irritation

Irritant for skin and mucous membranes.

· Serious eye damage or eye

irritation

Strong irritant with the danger of severe eye injury.

· Respiratory / skin sensitization

No sensitizing effect known.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 7)



Page 7/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 6)

Irritant

12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 1305-78-8 calcium oxide

EC50/72h | 184.57 mg/l (algae)

LC50/96h | 50.6 mg/l (Fis)

158 mg/l (Mew)

EC50/48h 49.1 mg/l (Freshwater)

NOEC 32 mg/l (Mew)

48 mg/l (algae)

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (Desmodesmus subspicatus)

LC50/96h >10000 mg/l (Oncorhynchus mykiss)

LC50/48h >1000 mg/l (Daphnia magna)

EC50/48h >1000 mg/l (Daphnia magna)

CAS: 497-19-8 Sodium carbonate

EC50/48h 265 mg/l (Daphnia magna)

EC50/96h 300 mg/l (Lepomis macrochirus)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· Additional ecological information:

· General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 8)



Page 8/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 7)

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14 Transportation information

14 Transportation information	
· UN-Number · ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · EHS reference list

CAS: 497-19-8 Sodium carbonate

- Directive 2012/18/EU
- · Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

(Contd. on page 9)



Page 9/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 35 Revision: 12.04.2025

Trade name MC-Fast RC

(Contd. of page 8)

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation – Category 1 Eye Irrit. 2: Serious eye damage or eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

- MY