

Page 1/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name MC-Fastpack PU Solid - Komponente B

Recommended use of the chemical and restrictions on

use No further relevant information available.

Application of the substance
/ the mixture Adhesives

Hardening agent/ Curing agent

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

2 Hazard identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergic or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

Hazard pictograms





GHS07 GHS08

· **Signal word** Danger

· Hazard-determining

components of labelling: diphenylmethanediisocyanate, isomeres and homologues

· Hazard statements Causes skin irritation.

(Contd. on page 2)



Page 2/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 1)

Causes serious eye irritation.

May cause allergic or asthma symptoms or breathing difficulties if

inhaled.

May cause allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure.

• **Precautionary statements** Do not breathe dust/fume/gas/mist/ vapours/spray.

Wear protective gloves / eye protection / face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Store in a well-ventilated place. Keep container tightly closed.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	30-60%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
67762-90-7	Siloxane und Silicone, di-Me, Reaktionsprodukte mit Siliciumdioxid	<2.5%
	Acute Tox. 4, H302	
4083-64-1	p-toluenesulphonyl isocyanate	≥0.1-<0.5%
	Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	

4 First-aid measures

· Description of first aid measures

• General information Instantly remove any clothing soiled by the product.

Take affected persons into the open air.

Seek medical treatment.

After inhalation
 After skin contact
 After eye contact
 Supply fresh air; consult doctor in case of symptoms.
 Instantly wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water.

Seek medical treatment.

(Contd. on page 3)



Page 3/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 2)

· After swallowing

Call a doctor immediately.

· Information for doctor

· Most important symptoms and effects, both acute and

delayed

No further relevant information available.

· Indication of any immediate medical attention and special

treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

· Protective equipment: Put on breathing apparatus.

6 Accidental release measures

· Personal precautions. protective equipment and

emergency procedures

Not required.

· Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 Handling and storage

Handling

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

(Contd. on page 4)



Page 4/9

Safety Data Sheet according to P.U.(A) 310/2013

Revision: 12.08.2023 Printing date 12.08.2023 Version number 24

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 3)

· Further information about

storage conditions: Keep container tightly sealed.

· Storage class

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative DNEL 0.05 mg/m³ (ArL)

PNECs

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew) 1 mg/l (Suw)

PNEC 1 mg/kg dwt (Bod)

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

Personal protective equipment

General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment: Respiratory protection is required at inadequately ventilated

workplaces and during spray processing. Fresh air masks or combination filters A2-P2 are recommended for short-term work.

· Protection of hands: Conditionally suitable materials for protective gloves; EN 374-3:

Nitrile rubber - NBR: Thickness ≥ 0.35mm.

Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be

changed immediately. Nitrile rubber, NBR

· Material of gloves

Penetration time of glove

material

The exact break trough time has to be found out by the

manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

Tightly sealed safety glasses.

(Contd. on page 5)



Page 5/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 4)

· **Body protection:** Protective work clothing.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid Colour: Grey

· Smell: Characteristic

· pH-value: Not determined.

· Change in condition

Melting point/freezing point 5-10 °C Initial boiling point and boiling range 190 °C

· Flash point: 201 °C

• Explosive properties: Product is not explosive.

· Steam pressure at 25 °C: 0 hPa

· Density at 20 °C 1.9 g/cm³

Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Viscosity:

dynamic at 20 °C: 130 mPas kinematic: Not determined.

· Other information

No further relevant information available.

10 Stability and reactivity

• Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous

reactions

Reacts with amines

• Conditions to avoid No further relevant information available.
• Incompatible materials: No further relevant information available.

(Contd. on page 6)



Page 6/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 5)

· Hazardous decomposition products:

No dangerous decomposition products known

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50	LD/LC50 values that are relevant for classification:				
Oral	LD50	>10000 mg/kg (Rat)			
Dermal	LD50	>5000 mg/kg (Kan)			
Inhalative	LC50/4 h	~450 mg/l (Rat)			

		I
9016-87-9	diphenyl	methanediisocyanate,isomeres and homologues
Oral	LD50	>10000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rab)
Inhalative	LC50/4 h	~450 mg/l (Rat)
67762-90-	7 Siloxan Silicium	e und Silicone, di-Me, Reaktionsprodukte mit ndioxid
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
4083-64-1	p-toluene	esulphonyl isocyanate
Oral	LD50	2600 mg/kg (rat)

· Primary irritant effect:

· **Skin corrosion or irritation** Irritant for skin and mucous membranes.

· Serious eye damage or eye

irritation Irritant effect.

Respiratory / skin

sensitizationSensitization possible by inhalation.
Sensitization possible by skin contact.

· Additional toxicological

information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Harmful Irritant

CMR effects (carcinogenity, mutagenicity and toxicity for

reproduction) Carc. 2

MY



Page 7/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 6)

12 Ecological information

· Toxicity

· Aquatic toxicity:

67762-90-7 Siloxane und Silicone, di-Me, Reaktionsprodukte mit

Siliciumdioxid

Sensitisation | EL50 | 10000 mg/l (Daphnien)

LC50/96h >10000 mg/l (Brachydanio rerio)

Persistence and degradability No further relevant information available.

· Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

Uncleaned packagings:

• Recommendation: Dispose of packaging according to regulations on the disposal of

packagings.

Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14 Transportation information

· UN-Number

· ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

(Contd. on page 8)



Page 8/9

Safety Data Sheet according to P.U.(A) 310/2013

Revision: 12.08.2023 Printing date 12.08.2023 Version number 24

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 7)

Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Ann	nex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

4083-64-1 p-toluenesulphonyl isocyanate

· Directive 2012/18/EU

· Named dangerous

None of the ingredients is listed. substances - ANNEX I

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4

(Contd. on page 9)



Page 9/9

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.08.2023 Version number 24 Revision: 12.08.2023

Trade name MC-Fastpack PU Solid - Komponente B

(Contd. of page 8)

Skin Irrit. 2: Skin corrosion or irritation – Category 2 Eye Irrit. 2: Serious eye damage or eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitization – Category 1 Skin Sens. 1: Skin sensitization – Category 1

Carc. 2: Carcinogenicity — Category 2 STOT SE 3: Specific target organ toxicity (single exposure) — Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) — Category 2

* Data compared to the previous version altered.

MY