



BE SURE. BUILD SURE.

Page 1/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

### 1 Identification of the hazardous chemical and of the supplier

· **Product identifier**

· **Trade name** MC-Injekt 2700 L - Komponente B

· **CAS Number:** 9016-87-9

· **Index number:** 615-005-01-6

· **Recommended use of the chemical and restrictions on use**

No further relevant information available.

· **Application of the substance / the mixture**

Injektion  
Polyurethane resin  
Hardening agent/ Curing agent

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

### 2 Hazard identification

· **Classification of the substance or mixture**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergic or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· **Label elements**

· **GHS label elements**

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word**

Danger

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

**Trade name MC-Injekt 2700 L - Komponente B**

(Contd. of page 1)

- **Hazard-determining components of labelling:** Diphenylmethane diisocyanate, isomers and homologues
- **Hazard statements**
  - H315 Causes skin irritation.
  - H319 Causes serious eye irritation.
  - H334 May cause allergic or asthma symptoms or breathing difficulties if inhaled.
  - H317 May cause allergic skin reaction.
  - H351 Suspected of causing cancer.
  - H335 May cause respiratory irritation.
  - H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
  - P260 Do not breathe dust/fume/gas/mist/ vapours/ spray.
  - P261 Avoid breathing dust/fume/ gas/mist/vapours/ spray.
  - P280 Wear protective gloves / eye protection / face protection.
  - P285 In case of inadequate ventilation wear respiratory protection.
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and information of the ingredients of the hazardous chemical

- **Chemical characterisation: Substances**
- **CAS No. Designation:** CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues
- **Identification number(s):**
- **Index number:** 615-005-01-6

### 4 First-aid measures

- **Description of first aid measures**
- **General information** Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.

(Contd. on page 3)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

**Trade name MC-Injekt 2700 L - Komponente B**

(Contd. of page 2)

- **After eye contact** *Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.*
- **After swallowing** *Do NOT induce vomiting. Rinse mouth with water. Medical attention required.*
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** *Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.*
- **Indication of any immediate medical attention and special treatment needed** *No information available.*

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **Special hazards arising from the substance or mixture** *Can be released in case of fire  
Carbon monoxide (CO)  
Nitrogen oxides (NOx)  
Hydrogen cyanide (HCN)  
Under certain fire conditions, traces of other toxic gases cannot be excluded.*
- **Advice for firefighters**
- **Protective equipment:** *Put on breathing apparatus.*

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** *Keep people at a distance and stay on the windward side.  
Put on breathing apparatus.*
- **Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **Reference to other sections** *See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.*

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

Trade name **MC-Injekt 2700 L - Komponente B**

See Section 13 for information on disposal.

(Contd. of page 3)

### 7 Handling and storage

· **Handling**

- **Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.  
For solid products: Avoid dust formation and dust deposits.  
Air limit values mentioned in section 8 must be monitored.  
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.  
For products containing solvents: Explosion protection required.  
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.  
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

· **Conditions for safe storage, including any incompatibilities**

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· **Storage**

· **Requirements to be met by storerooms and containers:**

Store only in the original container.

· **Further information about storage conditions:**

None.

· **Storage class**

10

· **Specific end use(s)**

No further relevant information available.

### 8 Exposure controls and personal protection

· **Additional information about design of technical systems:**

No further data; see section 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

Not required.

(Contd. on page 5)

MY



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

**Trade name MC-Injekt 2700 L - Komponente B**

(Contd. of page 4)

· **DNELs**

**CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

· **PNECs**

**CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues**

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

· **Additional information:**

The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

· **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

· **Protection of hands:**

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

**Trade name MC-Injekt 2700 L - Komponente B**

(Contd. of page 5)

- Example:**  
 Polychloroprene - CR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Nitrile rubber - NBR: thickness  $\geq 0.35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Fluoro rubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Recommendation: Dispose of contaminated gloves.  
 Polychloroprene - CR  
 Nitrile rubber - NBR  
 Butyl rubber - IIR  
 Fluoro rubber - FKM
- **Material of gloves**
  - **Penetration time of glove material**
  - **Eye protection:**
  - **Body protection:**
- Polychloroprene - CR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Nitrile rubber - NBR: thickness  $\geq 0.35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .  
 Fluoro rubber - FKM: Thickness  $\geq 0.4\text{mm}$ ; Breakthrough time  $\geq 480\text{min}$ .  
 Safety goggles with side protection in accordance with EN 166.  
 Use chemical-resistant protective clothing.  
 In case of hypersensitivity of the skin, handling the product is not recommended.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - **Form:** Fluid
  - **Colour:** Dark brown
  - **Smell:** Characteristic
- **pH-value:** Not determined.
- **Change in condition**
  - **Melting point/freezing point** Not determined
  - **Initial boiling point and boiling range** 330 °C
- **Flash point:** 204 °C
- **Auto-ignition temperature** >600 °C
- **Explosive properties:** Product is not explosive.
- **Steam pressure at 25 °C:** 0.0002 hPa
- **Density at 20 °C** 1.22 g/cm<sup>3</sup>

(Contd. on page 7)

MY



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

Trade name MC-Injekt 2700 L - Komponente B

(Contd. of page 6)

· **Solubility in / Miscibility with Water:**

Hydrolized  
Not miscible or difficult to mix  
Fully miscible

· **Viscosity:**  
dynamic at 20 °C:

200 mPas

· **Other information**

No further relevant information available.

#### 10 Stability and reactivity

· **Reactivity**

No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions**

Reacts with amines

· **Conditions to avoid**

No further relevant information available.

· **Incompatible materials:**

No further relevant information available.

· **Hazardous decomposition products:**

No dangerous decomposition products known

#### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

**CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues**

Oral LD50 >10000 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (Rab)

Inhalative LC50/4 h ~450 mg/l (Rat)

· **Primary irritant effect:**

· **Skin corrosion or irritation**

Irritant for skin and mucous membranes.

· **Serious eye damage or eye irritation**

Irritant effect.

· **Respiratory / skin sensitization**

Sensitization possible by inhalation.

Sensitization possible by skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:  
Harmful

(Contd. on page 8)



BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

Trade name MC-Injekt 2700 L - Komponente B

(Contd. of page 7)

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)** Carc. 2

#### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

#### 13 Disposal information

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### 14 Transportation information

- |                                     |      |
|-------------------------------------|------|
| · <b>UN-Number</b>                  |      |
| · <b>ADR, ADN, IMDG, IATA</b>       | Void |
| · <b>UN proper shipping name</b>    |      |
| · <b>ADR, ADN, IMDG, IATA</b>       | Void |
| · <b>Transport hazard class(es)</b> |      |
| · <b>ADR, ADN, IMDG, IATA</b>       |      |
| · <b>Class</b>                      | Void |
| · <b>Packing group</b>              |      |
| · <b>ADR, IMDG, IATA</b>            | Void |
| · <b>Environmental hazards:</b>     |      |
| · <b>Marine pollutant:</b>          | No   |

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025

Version number 40

Revision: 12.04.2025

**Trade name MC-Injekt 2700 L - Komponente B**

(Contd. of page 8)

- |   |                 |
|---|-----------------|
| · <b>Special precautions for user</b>                                       | Not applicable. |
| · <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>   | Void            |

#### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **EHS reference list**

Substance is not listed.

- **Directive 2012/18/EU**

- **Named dangerous**

**substances - ANNEX I** Substance is not listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

#### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:**

Environment protection department.

- **Contact:**

- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Irrit. 2: Skin corrosion or irritation – Category 2  
Eye Irrit. 2: Serious eye damage or eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitization – Category 1  
Skin Sens. 1: Skin sensitization – Category 1  
Carc. 2: Carcinogenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

- **\* Data compared to the previous version altered.**