



BE SURE. BUILD SURE.

Page 1/8

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29


Revision: 17.01.2025

1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name** **MC-Proof 601 HT**
- **Recommended use of the chemical and restrictions on use**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Sealing
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazard identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:** Portland cement
Fly ash Portland cement
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.
- **Precautionary statements** P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

(Contd. of page 1)

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- Chemical characterisation: Mixtures
- Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 14808-60-7	Quartz (SiO ₂)	30-60%
CAS: 65997-15-1	Portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥10-<20%
CAS: 1317-65-3	Calcium carbonate	10-30%
CAS: 68475-76-3	Fly ash Portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<1.5%

- Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information For all first aid measures: observe self-protection and consult a doctor!
- After inhalation Remove people from the dusty area.
- After skin contact Remove heavily soiled clothing. Clean with plenty of soap and water.
- After eye contact Rinse for 10 minutes under running water with the eyelids open. Always consult an ophthalmologist!
- After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/8

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Avoid dust formation! Avoid spraying the ready-to-use cementitious product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and after each break. Observe work restrictions!
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store bags tightly closed; protect from moisture and water!
Store containers tightly closed in a well-ventilated and well-lit room.
Access only for specialised personnel.
Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages, passageways and confined spaces.
- **Information about storage in one common storage facility:** Combined storage bans apply from a total storage quantity of 200 kg.
Do not store together with substances of the following LGK: 1; 6.2; 7
Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 5.1C
- **Further information about storage conditions:** Store in a dry and frost-free place.

(Contd. on page 4)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

· Storage class

13

(Contd. of page 3)

8 Exposure controls and personal protection

· **Additional information about**

design of technical systems: No further data; see section 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 14808-60-7 Quartz (SiO₂)

PEL (Malaysia) Long-term value: 0.1* mg/m³
*Pecahan ternafaskan

CAS: 65997-15-1 Portland cement

PEL (Malaysia) Long-term value: 10 mg/m³

CAS: 1317-65-3 Calcium carbonate

PEL (Malaysia) Long-term value: 10 mg/m³

· **DNELs**

CAS: 65997-15-1 Portland cement

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

· **PNECs**

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

· **Additional information:**

The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks!

Use skin care products after work (moisturising cream).

Change and clean heavily soiled clothing!

Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and after every break.

· **Breathing equipment:**

For work with higher dust loads particle filter class P2

· **Protection of hands:**

Check protective gloves prior to each use for their proper condition.

· **Material of gloves**

Nitrile impregnated cotton gloves.

· **Penetration time of glove material**

The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.

· **Eye protection:**

Safety glasses

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

· **Body protection:** Protective work clothing.

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Powder

· **Colour:** Grey

· **Smell:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

· **Melting point/freezing point** Not determined

· **Initial boiling point and boiling range** Not determined

· **Flash point:** Not applicable

· **Flammability** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Critical values for explosion:**

· **Lower:** Not determined.

· **Upper:** Not determined.

· **Steam pressure at 1732 °C:** 13.5 hPa

· **Density at 20 °C** 2.23 g/cm³

· **Settled apparent density** 1 kg/m³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Partly miscible

· **Partition coefficient: n-octanol/water** Not determined.

· **Viscosity:**

· **dynamic:** Not determined.

Not applicable.

· **kinematic:** Not determined.

Not applicable.

(Contd. on page 6)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values that are relevant for classification:**

CAS: 65997-15-1 Portland cement

Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	5 mg/l (rat)

CAS: 1317-65-3 Calcium carbonate

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Primary irritant effect:**
- **Serious eye damage or eye irritation** Strong irritant with the danger of severe eye injury.
- **Respiratory / skin sensitization** No sensitizing effect known.
- **Additional toxicological information:** The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

MY

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

(Contd. of page 6)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

CAS: 1317-65-3 Calcium carbonate

EC50/72h	>14 mg/l (Desmodesmus subspicatus)
LC50/96h	>10000 mg/l (Oncorhynchus mykiss)
LC50/48h	>1000 mg/l (Daphnia magna)
EC50/48h	>1000 mg/l (Daphnia magna)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal information

· **Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transportation information

· **UN-Number**
· **ADR, ADN, IMDG, IATA** Void

· **UN proper shipping name**
· **ADR, ADN, IMDG, IATA** Void

· **Transport hazard class(es)**
· **ADR, ADN, IMDG, IATA**
· **Class** Void

· **Packing group**
· **ADR, IMDG, IATA** Void

(Contd. on page 8)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 29

Revision: 17.01.2025

Trade name MC-Proof 601 HT

(Contd. of page 7)

- | | |
|---|-----------------|
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** *None of the ingredients is listed.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

- **Department issuing data specification sheet:** *Environment protection department.*
- **Contact:**
- **Abbreviations and acronyms:** *ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion or irritation – Category 2
Eye Dam. 1: Serious eye damage or eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**