

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Page 1/9

<b>T</b>	
Trade name Recommended use of the chemical and restrictions on	Nafufill KM 220
use Application of the substance	No further relevant information available.
/ the mixture	Concrete surfacer Ready-mixed mortar
<i>Details of the supplier of the s</i> <i>Manufacturer/Supplier:</i>	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10
	CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
Informing department: Hazard identification	msds@mc-bauchemie.de
Hazard identification Classification of the substand	ce or mixture
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin	ce or mixture irritation.
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes serio	<b>ce or mixture</b> irritation. bus eye damage.
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin	<b>ce or mixture</b> irritation. ous eye damage. espiratory irritation.
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes seric STOT SE 3 H335 May cause ro Label elements	<b>ce or mixture</b> irritation. ous eye damage. espiratory irritation.
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes seric STOT SE 3 H335 May cause re Label elements GHS label elements Hazard pictograms	ce or mixture irritation. ous eye damage. espiratory irritation. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes seric STOT SE 3 H335 May cause re Label elements GHS label elements Hazard pictograms Signal word	<b>ce or mixture</b> irritation. ous eye damage. espiratory irritation. The product is classified and labelled according to the Globa Harmonised System (GHS).
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes seric STOT SE 3 H335 May cause re Label elements GHS label elements Hazard pictograms	ce or mixture irritation. ous eye damage. espiratory irritation. The product is classified and labelled according to the Globa Harmonised System (GHS). GHS05 GHS07
Hazard identification Classification of the substand Skin Irrit. 2 H315 Causes skin Eye Dam. 1 H318 Causes seric STOT SE 3 H335 May cause re Label elements GHS label elements Hazard pictograms Signal word	<b>ce or mixture</b> <i>irritation.</i> <i>ous eye damage.</i> <i>espiratory irritation.</i> <i>The product is classified and labelled according to the</i> <i>Harmonised System (GHS).</i> <i>GHS05 GHS07</i>



Page 2/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

		(Contd. of page 1)
• Precautionary statements	P261	Avoid breathing dust/fume/ gas/mist/vapours/
		spray.
	P280	Wear protective gloves / eye protection / face
		protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for
		several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P321	Specific treatment (see on this label).
	P403+P233	Store in a well-ventilated place. Keep container
	1 100 11 200	tightly closed.
· Other hazards		ighty clocca.
• Results of PBT and vPvB ass		
· PBT:	Not applicable.	
· vPvB:	Not applicable.	

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

<ul> <li>Dangerous comp</li> </ul>	ponents:	
CAS: 14808-60-7	Quartz (SiO2)	50-70%
CAS: 65997-15-1		<i>≥</i> 20- <i>≤</i> 30%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 93685-99-5		<i>≥</i> 3-<10%
	STOT RE 2, H373; Eye Dam. 1, H318; STOT SE 3, H335	
CAS: 1305-62-0	Calcium dihydroxide	≥1-<2.5%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 93763-70-3	Perlite, expanded	<2.5%
CAS: 69012-64-2	amorphous silica (fume)	<2.5%
· Additional inform	nation For the wording of the listed hazard phrases refer to se	ction 16.

### 4 First-aid measures

General information	For all first aid measures: observe self-protection and consult a doctor!
After inhalation	Remove people from the dusty area.
After skin contact	Remove heavily soiled clothing. Clean with plenty of soap and water.
After eye contact	Rinse for 10 minutes under running water with the eyelids open. Always consult an ophthalmologist!
	(Contd. on page 3)



Page 3/9

MY

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

· After swallowing

(Contd. of page 2) Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

#### 5 Fire-fighting measures

• Extinguishing media

· Protective equipment:

- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · Special hazards arising from
- the substance or mixture No further relevant information available. • Advice for firefighters
  - No special measures required.

#### 6 Accidental release measures

<ul> <li>Personal precautions, protective equipment and</li> </ul>	
emergency procedures	Not required.
Environmental precautions:	No special measures required.
Methods and material for	
containment and cleaning up.	: Collect mechanically.
<ul> <li>Reference to other sections</li> </ul>	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	See Section 13 for information on disposal.

#### 7 Handling and storage

· Handling

• **Precautions for safe handling** Avoid dust formation! Avoid spraying the ready-to-use cementitious product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and after each break. Observe work restrictions!

· Conditions for safe storage, including any incompatibilities

· Storage

 Requirements to be met by storerooms and containers:
 Store bags tightly closed; protect from moisture and water! Store containers tightly closed in a well-ventilated and well-lit room. Access only for specialised personnel. Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages, passageways and confined spaces.
 Information about storage in one common storage facility:
 Combined storage bans apply from a total storage quantity of 200 kg. Do not store together with substances of the following LGK: 1; 6.2; 7



Page 4/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

(Contd. of page 3) Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 5.1C

· Further information about storage conditions: Storage class

Store in a dry and frost-free place. 13

## 8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see section 7.

#### · Control parameters

· Components with critical values that require monitoring at the workplace:

PEL (Malaysia) Long-term value: 0.1\* mg/m<sup>3</sup> \*Pecahan ternafaskan

CAS: 65997-15-1 Portland cement

PEL (Malaysia) Long-term value: 10 mg/m<sup>3</sup>

CAS: 1305-62-0 Calcium dihydroxide

PEL (Malaysia) Long-term value: 5 mg/m<sup>3</sup>

CAS: 93763-70-3 Perlite, expanded

PEL (Malaysia) Long-term value: 10 mg/m<sup>3</sup>

CAS: 69012-64-2 amorphous silica (fume)

PEL (Malaysia) Long-term value: 2\* mg/m<sup>3</sup> wasap; \*Pecahan ternafaskan

#### · DNELs

CAS: 65997-15-1 Portland cement

Inhalative DNEL 1 mg/m<sup>3</sup> (ArL)

CAS: 93685-99-5 Burnt oil shale

Inhalative DNEL 0.233 mg/m<sup>3</sup> (ArL)

CAS: 1305-62-0 Calcium dihydroxide

Inhalative DNEL 1 mg/m<sup>3</sup> (ArL) PNECs

CAS: 93685-99-5 Burnt oil shale

PNEC 100 mg/l (BEL)

0.002 mg/l (Mew)

0.02 mg/l (Freshwater)

CAS: 1305-62-0 Calcium dihydroxide

PNEC 3 mg/l (BEL)

0.32 mg/l (Mew)

0.49 mg/l (Freshwater)

PNEC 1080 mg/kg dwt (Bod)

(Contd. on page 5)



Page 5/9

MY

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

· Additional information:	(Contd. of page 4) The lists that were valid during the compilation were used as basis.
• Exposure controls • Personal protective equipme	ent
General protective and	<b>-</b>
hygienic measures	Do not store food, eat, drink, sniff or smoke in the work area! Avoid contact with eyes and skin!
	Clean hands thoroughly at the end of work and before breaks! Use skin care products after work (moisturising cream). Change and clean heavily soiled clothing!
	Change clothes at the end of work!
	Apply greasy skin protection ointment before starting work and after every break.
· Breathing equipment:	For work with higher dust loads particle filter class P2
· Protection of hands:	Check protective gloves prior to each use for their proper condition.
• Material of gloves	Nitrile impregnated cotton gloves.
Penetration time of glove	The second burght through the second be able to all forms the most set to a
material	The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
• Eye protection:	Safety glasses
Body protection:	Protective work clothing.

## 9 Physical and chemical properties

Appearance:	Develop	
Form: Colour:	Powder Grey	
Smell:	Odourless	
pH-value:	Not applicable.	
Change in condition Melting point/freezing point Initial boiling point and boiling	Not determined <b>range</b> 2230 °C	
Flash point:	Not applicable	
Auto-ignition temperature	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Steam pressure at 1732 °C:	13.5 hPa	
Density	Not determined	
Solubility in / Miscibility with Water:	Unsoluble	
Viscosity: dynamic:	Not applicable.	



Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

(Contd. of page 5)

Trade name Nafufill KM 220

kinematic:

Not applicable.

· Other information

No further relevant information available.

D			No further relation to the second in the second in the	
Reactivity Chemical			No further relevant information available.	
Thermal c	stability lecompos	sition /		
condition			No decomposition if used according to specifications.	
Possibility of hazardous reactions Conditions to avoid Incompatible materials:		rdous	No dangerous reactions known	
		.1		
			No further relevant information available. No further relevant information available.	
Hazardou				
products:			No dangerous decomposition products known	
Toxicol	o <mark>gical i</mark> n	oformatio	วท	
Informatio	on on tox	icological	effects	
Acute tox	•	-		
LD/LC50 v	values tha	at are relev	vant for classification:	
CAS: 659	97-15-1 P	ortland ce	ment	
Dermal	LD50	2000 mg/	2000 mg/kg (rabbit)	
Inhalative LC50/4 h 5 mg/l (rat,		5 mg/l (ra	<i>t</i> )	
CAS: 936	85-99-5 B	urnt oil sh	nale	
Oral	LD50	>2000 mg	>2000 mg/kg (rat)	
Inhalative	LOAEL	0.000699	mg/l (ArL)	
CAS: 130	5-62-0 Ca	İcium dihy	/droxide	
Oral	LD50	7340 mg/	/kg (rat)	
Primary ir	ritant effe	ect:		
Skin corre			Irritant for skin and mucous membranes.	
Serious e	ye aamag	je or eye	Strong irritant with the danger of severe eye injury.	
Respirato	rv / skin			
sensitizat			No sensitizing effect known.	
Additiona		gical	-	
information:			The product shows the following dangers according to the calculation method of the General EC Classification Guidelines to Preparations as issued in the latest version:	

Page 6/9



Page 7/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

(Contd. of page 6)

· Aquatic te	oxicity:	
CAS: 936	85-99-5 Burnt oil sl	nale
EC50/72h	82.7 mg/l (Selenas	trum capricornutum)
LC50/96h	>100 mg/l (fish)	
EC50/48h	>100 mg/l (Daphnia	a magna)
NOEC	>100 mg/l (fish)	
CAS: 690	12-64-2 amorphous	s silica (fume)
EC50/24h	>1002 mg/l (Daphr	ia magna)
NOEC	319 mg/l (Daphnia	magna)
<ul> <li>Bioaccum</li> <li>Mobility in</li> </ul>		No further relevant information available. No further relevant information available.
· General n		Do not allow undiluted product or large quantities of it to reac ground water, water bodies or sewage system.
	f PBT and vPvB as	
· PBT:		Not applicable.
· vPvB: · Other adv	verse effects	Not applicable. No further relevant information available.

Uncleaned packagings:
 Recommendation:

*Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.* 

· UN-Number		
ADR, ADN, IMDG, IATA	Void	
UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	

allow product to reach sewage system.



Page 8/9

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Trade name Nafufill KM 220

		(Contd. of page
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous
- substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

<ul> <li>Department issuing data specification sheet:</li> <li>Contact:</li> </ul>	Environment protection department.
• Abbreviations and acronyms:	<ul> <li>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)</li> <li>ICAO: International Civil Aviation Organisation</li> <li>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</li> <li>IMDG: International Maritime Code for Dangerous Goods</li> <li>IATA: International Air Transport Association</li> <li>EINECS: European Inventory of Existing Commercial Chemical Substances</li> <li>ELINCS: European List of Notified Chemical Substances</li> <li>CAS: Chemical Abstracts Service (division of the American Chemical Society)</li> <li>DNEL: Derived No-Effect Level (REACH)</li> <li>PNEC: Predicted No-Effect Concentration (REACH)</li> <li>LC50: Lethal concentration, 50 percent</li> <li>LD50: Lethal dose, 50 percent</li> <li>PBT: Persistent, Bioaccumulative and Toxic</li> <li>vPvB: very Persistent and very Bioaccumulative</li> </ul>
	(Contd. on page 9)



# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 17.01.2025

Version number 35

Revision: 17.01.2025

Page 9/9

Trade na

name Nafufill KM 220		
ata compared to the	(Contd. of page 8) Skin Irrit. 2: Skin corrosion or irritation – Category 2 Eye Dam. 1: Serious eye damage or eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	

· \* Dat previous version altered.