

Page 1/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

#### 1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name Nafufill KM 250 HS

Recommended use of the chemical and restrictions on

use No further relevant information available.

· Application of the substance / the mixture

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Concrete surfacer

· Informing department: msds@mc-bauchemie.de

#### 2 Hazard identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms

GHS05 GHS07

· Signal word Danger

Hazard-determining

components of labelling: Portland cement (low chromate)

Burnt oil shale

Flue dust, portland cement H315 Causes skin irritation.

Hazard statements
 H315 Causes skin irritation.
 H318 Causes serious eye damage.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 1)

· Precautionary statements P261 Avoid breathing dust/fume/ gas/mist/vapours/

spray.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).
P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## 3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 14808-60-7	Quartz sand	50-70%
CAS: 65997-15-1	Portland cement (low chromate)	≥20-≤30%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 93685-99-5		≥3-<10%
	STOT RE 2, H373; Eye Dam. 1, H318; STOT SE 3, H335	
CAS: 69012-64-2	amorphous silicon dioxide	<2.5%
CAS: 68475-76-3	Flue dust, portland cement	≥1-<1.5%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	

· Additional information For the wording of the listed hazard phrases refer to section 16.

# 4 First-aid measures

Description of first aid measures

· General information For all first aid measures: observe self-protection and consult a

doctor!

· After inhalation Remove people from the dusty area.

After skin contact Remove heavily soiled clothing. Clean with plenty of soap and

water.

· After eye contact Rinse for 10 minutes under running water with the eyelids open.

Always consult an ophthalmologist!

• After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

- MY



Page 3/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

Trade name Nafufill KM 250 HS

(Contd. of page 2)

#### 5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Not required.

· Environmental precautions: No special measures required.

· Methods and material for

containment and cleaning up: Collect mechanically.

Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### 7 Handling and storage

· Handling

· Precautions for safe handling Avoid dust formation! Avoid spraying the ready-to-use cementitious

product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and

after each break. Observe work restrictions!

Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Store bags tightly closed; protect from moisture and water!

Store containers tightly closed in a well-ventilated and well-lit room.

Access only for specialised personnel.

Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages,

passageways and confined spaces.

Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

Do not store together with substances of the following LGK: 1; 6.2;

Storage with substances of the following LGK is only possible

under the conditions specified in TRGS 510: 4.1A; 5.1C

(Contd. on page 4)



Page 4/8

# Safety Data Sheet according to P.U.(A) 310/2013

Revision: 12.04.2025 Printing date 12.04.2025 Version number 52

#### Trade name Nafufill KM 250 HS

(Contd. of page 3)

· Further information about

storage conditions:

Store in a dry and frost-free place.

· Storage class

### 8 Exposure controls and personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 14808-60-7 Quartz sand

PEL (Malaysia) Long-term value: 0.1\* mg/m³

\*Pecahan ternafaskan

CAS: 65997-15-1 Portland cement (low chromate)

PEL (Malaysia) Long-term value: 10 mg/m<sup>3</sup>

CAS: 69012-64-2 amorphous silicon dioxide

PEL (Malaysia) Long-term value: 2\* mg/m³

wasap; \*Pecahan ternafaskan

DNELs

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL) CAS: 93685-99-5 Burnt oil shale

Inhalative DNEL 0.233 mg/m³ (ArL)

· PNECs

CAS: 93685-99-5 Burnt oil shale

PNEC 100 mg/l (BEL)

0.002 mg/l (Mew)

0.02 mg/l (Freshwater)

Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks! Use skin care products after work (moisturising cream).

Change and clean heavily soiled clothing!

Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and

after every break.

For work with higher dust loads particle filter class P2 · Breathing equipment:

· Protection of hands: Check protective gloves prior to each use for their proper condition.

· Material of gloves Nitrile impregnated cotton gloves.

(Contd. on page 5)



Page 5/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 4)

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

Eye protection: Safety glasses

· Body protection: Protective work clothing.

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder
Colour: Whitish
Smell: Odourless

· pH-value at 20 °C:

· Change in condition

Melting point/freezing point Not determined

Initial boiling point and boiling range 2230 °C

• Flash point:

Not applicable

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Steam pressure at 1732 °C: 13.5 hPa

· Density at 20 °C 2.74 g/cm³

· Solubility in / Miscibility with

Water: Unsoluble

· Viscosity:

dynamic:Not applicable.kinematic:Not applicable.

· Other information No further relevant information available.

11

### 10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous

reactions No dangerous reactions known

• Conditions to avoid No further relevant information available. • Incompatible materials: No further relevant information available.

(Contd. on page 6)



Page 6/8

# Safety Data Sheet according to P.U.(A) 310/2013

Revision: 12.04.2025 Printing date 12.04.2025 Version number 52

Trade name Nafufill KM 250 HS

(Contd. of page 5)

· Hazardous decomposition products:

No dangerous decomposition products known

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values that are relevant for classification:

CAS: 65997-15-1 Portland cement (low chromate)

2000 mg/kg (rabbit) Dermal LD50

Inhalative LC50/4 h 5 mg/l (rat)

CAS: 93685-99-5 Burnt oil shale

LD50 >2000 mg/kg (rat) Oral Inhalative LOAEL 0.000699 mg/l (ArL)

Primary irritant effect:

· Skin corrosion or irritation

Irritant for skin and mucous membranes.

· Serious eye damage or eye

irritation · Respiratory / skin

sensitization

information:

Additional toxicological

Strong irritant with the danger of severe eye injury.

No sensitizing effect known.

The product shows the following dangers according to the

calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version: Irritant

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### CAS: 93685-99-5 Burnt oil shale

EC50/72h 82.7 mg/l (Selenastrum capricornutum)

LC50/96h >100 mg/l (fish)

EC50/48h >100 mg/l (Daphnia magna)

NOEC >100 mg/l (fish)

CAS: 69012-64-2 amorphous silicon dioxide

EC50/24h >1002 mg/l (Daphnia magna) NOEC 319 mg/l (Daphnia magna)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)



Page 7/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 6)

· Additional ecological information:

General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Other adverse effects No further relevant information available.

### 13 Disposal information

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Non contaminated packagings can be used for recycling.

## 14 Transportation information

· UN-Number · ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· Packing group · ADR, IMDG, IATA	Void	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex II of  Marpol and the IBC Code  Not applicable.		
· UN "Model Regulation":	Void	

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous

**substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 8)



Page 8/8

# Safety Data Sheet according to P.U.(A) 310/2013

Printing date 12.04.2025 Version number 52 Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 7)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion or irritation - Category 2

Eye Dam. 1: Serious eye damage or eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

\* \* Data compared to the previous version altered.