



BE SURE. BUILD SURE.

Page 1/8

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29


Revision: 13.04.2025

1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name** **Oxal SM TK 5**
- **Recommended use of the chemical and restrictions on use**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Ready-mixed mortar
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazard identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:** Portland cement (low chromate)
Calcium hydroxide
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.
- **Precautionary statements** P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

MY



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 1)

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- Chemical characterisation: Mixtures
- Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 14808-60-7	Quartz (SiO ₂)	60-80%
CAS: 1317-65-3	Calcium carbonate	10-30%
CAS: 65997-15-1	Portland cement (low chromate) Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥3-<10%
CAS: 1305-62-0	Calcium hydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥3-<5%

- Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information For all first aid measures: observe self-protection and consult a doctor!
- After inhalation Remove people from the dusty area.
- After skin contact Remove heavily soiled clothing. Clean with plenty of soap and water.
- After eye contact Rinse for 10 minutes under running water with the eyelids open. Always consult an ophthalmologist!
- After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** Collect mechanically.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Avoid dust formation! Avoid spraying the ready-to-use cementitious product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and after each break. Observe work restrictions!
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store bags tightly closed; protect from moisture and water!
Store containers tightly closed in a well-ventilated and well-lit room.
Access only for specialised personnel.
Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages, passageways and confined spaces.
- **Information about storage in one common storage facility:** Combined storage bans apply from a total storage quantity of 200 kg.
Do not store together with substances of the following LGK: 1; 6.2; 7
Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 5.1C
- **Further information about storage conditions:** Store in a dry and frost-free place.
- **Storage class** 13

MY

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 3)

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 14808-60-7 Quartz (SiO₂)

PEL (Malaysia) Long-term value: 0.1* mg/m³
*Pecahan ternafaskan

CAS: 1317-65-3 Calcium carbonate

PEL (Malaysia) Long-term value: 10 mg/m³

CAS: 65997-15-1 Portland cement (low chromate)

PEL (Malaysia) Long-term value: 10 mg/m³

CAS: 1305-62-0 Calcium hydroxide

PEL (Malaysia) Long-term value: 5 mg/m³

· **DNELs**

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1305-62-0 Calcium hydroxide

Inhalative DNEL 1 mg/m³ (ArL)

· **PNECs**

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

CAS: 1305-62-0 Calcium hydroxide

PNEC 3 mg/l (BEL)

0.32 mg/l (Mew)

0.49 mg/l (Freshwater)

PNEC 1080 mg/kg dwt (Bod)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks!

Use skin care products after work (moisturising cream).

Change and clean heavily soiled clothing!

Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 4)

- **Breathing equipment:** after every break.
For work with higher dust loads particle filter class P2
- **Protection of hands:** Check protective gloves prior to each use for their proper condition.
- **Material of gloves:** Nitrile impregnated cotton gloves.
- **Penetration time of glove material:** The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder

Colour: Grey

· Smell: Characteristic

· Odour threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/freezing point Not determined

Initial boiling point and boiling range 2230 °C

· Flash point: Not applicable

· Flammability: Not determined.

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive.

· Critical values for explosion:

Lower: Not determined.

Upper: Not determined.

· Steam pressure at 1732 °C: 13.5 hPa

· Density at 20 °C 2.67 g/cm³

· Relative density: Not determined.

· Vapour density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Insoluble

· Partition coefficient: n-octanol/water Not determined.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 5)

- **Viscosity:**
dynamic: Not applicable.
kinematic: Not applicable.
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

CAS: 1317-65-3 Calcium carbonate

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

CAS: 65997-15-1 Portland cement (low chromate)

Dermal LD50 2000 mg/kg (rabbit)

Inhalative LC50/4 h 5 mg/l (rat)

CAS: 1305-62-0 Calcium hydroxide

Oral LD50 7340 mg/kg (rat)

- **Primary irritant effect:**
- **Serious eye damage or eye irritation** Strong irritant with the danger of severe eye injury.
- **Respiratory / skin sensitization** No sensitizing effect known.

MY

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 6)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (*Desmodesmus subspicatus*)

LC50/96h >10000 mg/l (*Oncorhynchus mykiss*)

LC50/48h >1000 mg/l (*Daphnia magna*)

EC50/48h >1000 mg/l (*Daphnia magna*)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal information

· **Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transportation information

· **UN-Number**

· **ADR, IMDG, IATA** Void

· **UN proper shipping name**

· **ADR, IMDG, IATA** Void

· **Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class** Void

· **Packing group**

· **ADR, IMDG, IATA** Void

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 13.04.2025

Version number 29

Revision: 13.04.2025

Trade name Oxal SM TK 5

(Contd. of page 7)

- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **UN "Model Regulation":** Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **EHS reference list**

None of the ingredients is listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:** Environment protection department.
- **Contact:**
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Skin Irrit. 2: Skin corrosion or irritation – Category 2
 - Eye Dam. 1: Serious eye damage or eye irritation – Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**